

Standard Container Specifications

NOTE: average specifications are given as an indication only. Variations can be found between shipping lines, series and make s.



General Purpose

- Suitable for general cargo
- Floor height approx. 170mm
- Lashing rings on internal sides
- Lashing devices load approx. 1000kg each

Type	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Capacity	Tare Weight	Maximum Pay-load
20'	5900mm	2352mm	2395mm	2340mm	2292mm	33.2m3	2350kg	28130kg
40'	12032mm	2352mm	2390mm	2340mm	2292mm	67.7m3	3750kg	28750kg



High Cube

- Designed for voluminous cargo up to 2.70m height
- Floor height approx. 170mm
- Lashing rings on internal sides
- Lashing devices load approx. 1000kg each
- NOTE: consider over-height for inland transportation

Type	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Capacity	Tare Weight	Maximum Pay-load
40'	12032mm	2350mm	2700mm	2340mm	2597mm	76.3m3	3900kg	28600kg



Open Top

- Designed for cargo loaded from door or top side (e.g. by crane)
- Covered by tarpaulin
- Floor height approx. 170mm
- Lashing rings on internal sides
- Lashing devices load approx. 1000kg each

Type	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Capacity	Tare Weight	Maximum Pay-load
20'	5895mm	2350mm	2340mm	2338mm	2280mm	32.5m3	2450kg	30050kg
40'	12029mm	2350mm	2380mm	2340mm	2276mm	66.8m3	4050kg	28450kg

Standard Container Specifications

NOTE: average specifications are given as an indication only. Variations can be found between shipping lines, series and make s.



Flat Rack

- Designed for heavy loads and oversize cargo
- Also available as collapsible Flat Rack, usually with spring assisted end walls
- Lashing points on corner posts, rails and floor
- Lashing devices load approx. 5000kg each

Type	Inside Length	Inside Width	Inside Height	Door Width	Door Height	Capacity	Tare Weight	Maximum Pay-load
20'	6038mm	2438mm	2233mm	--	--	variable	2900kg	42100kg
40'	12048mm	2347mm	2265mm	--	--	variable	5900kg	49100kg